



UNIVERSITI PUTRA MALAYSIA

**THEORY AND SIMULATION OF THE ONSETS OF CONVECTION
INDUCED BY LIQUID DIFFUSION IN LIQUID AND INCIPIENT
INSTABILITY CAUSED BY LIQUID FLOW PARTICLE BED**

SIEW FONG WAH.

FK 2006 45

**THEORY AND SIMULATION OF THE ONSETS OF CONVECTION
INDUCED BY LIQUID DIFFUSION IN LIQUID AND INCIPIENT
INSTABILITY CAUSED BY LIQUID FLOW IN PARTICLE BED**

By

SIEW FONG WAH

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia,
in Fulfilment of the Requirements for the Degree of Master of Science**

March 2006



To Dad and Mom



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment
of the requirement for the degree of Master of Science

**THEORY AND SIMULATION OF THE ONSETS OF CONVECTION
INDUCED BY LIQUID DIFFUSION IN LIQUID AND
INCIPIENT INSTABILITY CAUSED BY
LIQUID FLOW IN PARTICLE BED**

By

SIEW FONG WAH

March 2006

Chairman: Associate Professor Thomas Choong Shean Yaw, PhD

Faculty: Engineering

The theory of transient instability of gas in aqueous liquid proposed by Tan and Thorpe (1999) was extended to study the onset of convection induced by liquid diffusion in liquid. 2D time-dependent simulations were conducted using a CFD package – FLUENT to verify the analysis of transient instability. The onset of buoyancy convection induced by liquid mass diffusion was simulated for water diffused into 1-butanol, ethyl acetate and 2-butanone at different temperatures. The formation and the development of the convection plumes were successfully simulated. The transient liquid diffusion simulation was verified using Fick's Law. The average simulated transient Rayleigh number was found to be 1315, which was close to 1404, i.e. the average value of critical Rayleigh number of 1100 and 1708 for boundary conditions with free-solid and solid-solid surfaces. The simulated onset time, the critical diffusion depth and the size of the plumes were found to agree well with values predicted by theory.

By recognizing that the mass transfer effect is very much smaller compared to the effect of momentum diffusion in causing the incipient instability in particle bed, the transient critical Rayleigh number proposed by Tan (2004) was re-defined based on momentum diffusion. The time-dependent simulations for incipient instability caused by liquid flow in particle bed were performed for different particle sizes, flow rates and initial bed heights. The CFD simulations were verified by the variation of particle bed height with superficial velocity. The onset time of incipient instability could be determined by the series contours of volume fraction, velocity vectors and maximum velocity. The simulated critical Rayleigh numbers based on the momentum diffusion were found to be inconsistent. A modified critical Rayleigh number was proposed by incorporating a factor of z_c/H to the critical Rayleigh number. The simulated modified critical Rayleigh number was found to be almost constant, $Ra_c' = 16.8$, which was very close to the theoretical value of 17.7 for buoyancy instability for porous media.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia
sebagai memenuhi keperluan untuk ijazah Master Sains

**TEORI DAN SIMULASI UNTUK PERMULAAN PEROLAKAN
DISEBABKAN OLEH RESAPAN CECAIR DALAM CECAIR
DAN INSIPIEN KETIDAKSTABILAN DISEBABKAN OLEH
ALIRAN CECAIR DALAM LAPISAN BUTIRAN**

Oleh

SIEW FONG WAH

Mac 2006

Pengerusi: Profesor Madya Thomas Choong Shean Yaw, PhD

Faculti: Kejuruteraan

Teori transien ketidakstabilan gas dalam cecair akueus yang dicadang oleh Tan and Thorpe (1999) disambung untuk mengkaji permulaan perolakan yang disebabkan oleh resapan cecair dalam cecair. Simulasi 2D bergantung masa telah dilakukan dengan menggunakan pakej CFD – FLUENT untuk mengesahkan analisa ketidakstabilan transien. Permulaan perolakan pengapungan yang disebabkan oleh resapan jisim cecair telah disimulasi untuk resapan air ke dalam 1-butanol, etil asetat dan 2-butanol pada suhu yang berlainan. Pembentukan dan perkembangan *plume* perolakan yang disebabkan oleh resapan jisim transien apabila cecair meresap ke dalam cecair berlainan telah disimulasi dengan berjaya. Simulasi resapan cecair transien disahkan dengan menggunakan Hukum *Fick*. Purata nombor *Rayleigh* transien yang disimulasikan adalah 1315, hampir dengan 1404, iaitu nilai purata nombor *Rayleigh* kritikal 1100 and 1708 untuk keadaan sempadan dengan permukaan bebas-pepejal dan pepejal-pepejal. Masa permulaan, kedalaman resapan kritikal dan saiz *plume* yang disimulasi didapati bersetuju dengan nilai yang diramal daripada teori.

Dengan pengetahuan bahawa kesan pemindahan jisim adalah sangat kecil berbanding dengan kesan resapan momentum dalam menyebabkan insipien ketidakstabilan dalam lapisan butiran, nombor *Rayleigh* kritikal transien yang dicadangkan oleh Tan (2004) didefinisikan semula berdasarkan resapan momentum. Simulasi bergantung masa untuk insipien ketidakstabilan yang disebabkan oleh aliran cecair dalam lapisan butiran dilakukan untuk pelbagai saiz butiran, kadar aliran dan ketinggian lapisan butiran awal. Simulasi CFD disahkan dengan perubahan ketinggian lapisan butiran dengan halaju superfisial. Masa permulaan insipien ketidakstabilan dapat ditentukan dengan siri kontur pecahan isipadu, vektor halaju dan halaju maksimum. Nombor *Rayleigh* kritikal berdasarkan resapan momentum yang disimulasi didapati adalah tidak tetap. Nombor *Rayleigh* kritikal yang diubahsuai dicadang dengan menggabungkan faktor z_c/H kepada nombor *Rayleigh* kritikal. Nombor *Rayleigh* kritikal diubahsuai yang disimulasi didapati adalah tetap, $Ra_c' = 16.8$, sangat hampir dengan nilai teori 17.7 untuk ketidakstabilan pengapungan untuk poros media.

ACKNOWLEDGEMENT

It is with profound gratitude that I would like to thank my esteemed supervisor and mentor, Associate Professor Dr. Thomas Choong Shean Yaw and Professor Ir. Dr. Tan Ka Kheng, for their constructive input, thoughtful comments, brilliant guidance and patient supervision of my work.

Heartfelt thanks towards Mr. Tan Yee Wan who had tirelessly taught me to master the simulation package, Mr. Sreenivas, support and consulting engineer in FLUENT (India), and Mr. Look Kar Yang for their valuable suggestions and advices in conducting my simulation. Also my thanks to Dr. Siti Aslina, Dr. Mohamad Amran, Dr. Tay and Dr. Ling for their generous advices in helping me to materialize my theses.

Lastly, I would like to thank my friends for their encouragement throughout the course of this project.

I certify that an Examination Committee has met on 23rd March 2006 to conduct the final examination of Siew Fong Wah on his Master of Science thesis entitled "Theory and Simulation of the Onsets of Convection Induced by Liquid Diffusion in Liquid and Incipient Instability Caused by Liquid Flow in Particle Bed" in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows:

Suraya Abdul Rashid, PhD

Lecturer

Faculty of Engineering

Universiti Putra Malaysia

(Chairman)

Luqman Chuah b. Abdullah, PhD

Associate Professor

Faculty of Engineering

Universiti Putra Malaysia

(Internal Examiner)

Mohamad Amran Mohd. Salleh, PhD

Lecturer

Faculty of Engineering

Universiti Putra Malaysia

(Internal Examiner)


Wang Chi Hwa, PhD

Associate Professor

Faculty of Engineering

National University of Singapore

(External Examiner)


HASANAH MOHD. GHAZALI, PhD
Professor/Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: **11 JUL 2006**

This thesis submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfilment of the requirement for the degree of Master of Science. The members of the Supervisory Committee are as follows:

Thomas Choong Shean Yaw, PhD

Associate Professor

Faculty of Engineering

Universiti Putra Malaysia

(Chairman)

Siti Aslina Hussain, PhD

Lecturer

Faculty of Engineering

Universiti Putra Malaysia

(Member)



AINI IDERIS, PhD

Professor/Dean

School of Graduate Studies

Universiti Putra Malaysia

Date: 10 AUG 2006

DECLARATION

I hereby declare that the thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institutions.


SIEW FONG WAH

Date: 13 JULY 2006.

TABLE OF CONTENTS

	DEDICATION	Page
	ABSTRACT	ii
	ABSTRAK	iii
	ACKNOWLEDGEMENT	v
	APPROVAL	vii
	DECLARATION	viii
	LIST OF TABLES	x
	LIST OF FIGURES	xiv
	LIST OF ABBREVIATIONS/NOMENCLATURE	xv
		xvii
CHAPTER		
1	INTRODUCTION	1.1
2	LITERATURE REVIEW	2.1
	2.1 Introduction	2.1
	2.2 Theory of Transient Instabilities and Convection	2.1
	2.3 Experimental Studies of Convection Caused by Density Gradient	2.4
	2.4 Instabilities in Fluidized Bed	2.10
	2.5 Flow Pattern in Liquid Fluidized Bed	2.15
	2.6 Overview	2.16
3	DEVELOPMENT OF THE TRANSIENT INSTABILITY THEORY	3.1
	3.1 Introduction	3.1
	3.2 The Onset of Buoyancy Convection Induced by Transient Liquid Diffusion in Liquid	3.2
	3.2.1 Fixed Surface Concentration (FSC) Boundary Condition	3.3
	3.2.2 Determination of Saturated Concentration and Molar Density Coefficient of Liquid in Liquid	3.5
	3.3 The Onset of Incipient Instability Caused by Liquid flow in Particle Bed	3.7
	3.3.1 Minimum Fluidization Velocity	3.10
	3.4 Overview	3.11
4	MATERIALS AND METHODOLOGY	4.1
	4.1 Computational Fluid Dynamics (CFD) Simulations	4.1
	4.2 Overall Solution Algorithm	4.2
	4.3 Simulation of Species Transport Model for Buoyancy Convection Induced by Transient Mass Diffusion in Liquid	4.4
	4.3.1 Conservation of Mass, Heat and Momentum Transfer Used in Species Transport Model	4.4



4.4	Simulation of Eulerian Multiphase Model for Incipient Fluidization Caused by Liquid Flow in Particle Bed	4.5
4.4.1	Conservation Equations in Eulerian Multiphase Model	4.6
4.4.2	Fluid-Solid Exchange Coefficient for Fluidized Bed	4.6
4.5	Numerical Considerations and Constrains in CFD Simulation	4.8
4.6	Simulations Setup	4.10
4.6.1	Determination of Physical Properties for the Onset of Convection caused by Liquid Diffusion in Liquid	4.11
4.6.2	Simulation Setup for the Onset of Convection Caused by Liquid Diffusion in Liquid	4.12
4.6.3	Simulation Setup for the Onset of Incipient Fluidization Caused by Liquid Flow in Particle Bed	4.15
4.7	Overview	4.18
5	RESULTS AND DISCUSSIONS	5.1
5.1	Introduction	5.1
5.2	Simulations of the Onset of Buoyancy Convection Caused by Liquid Diffusion in Liquid	5.1
5.2.1	Transient Rayleigh Number for Onset of Convection	5.3
5.2.2	Critical Time for the Onset of Convection	5.4
5.2.3	Evolution of the Convection Plumes	5.5
5.2.4	Critical Penetration Depths and Critical Wavelength	5.9
5.2.5	Maximum Velocity of Convection	5.12
5.2.6	Mass Flux and Mass Transfer Coefficient	5.13
5.3	Simulations of the Onset of Incipient Fluidization Caused by Liquid Flow in Particle Bed	5.15
5.3.1	Simulated Flow Behaviour and the Onset of Incipient Fluidization Caused by Liquid Flow in Particle Bed	5.16
5.3.2	Maximum Velocity for Liquid Flow through Particle Bed	5.23
5.3.3	Critical Rayleigh Number and Onset Time of Incipient Instability	5.25
5.4	Overview	5.28
6	CONCLUSIONS	6.1
7	RECOMMENDATIONS	7.1

REFERENCES	R.1
APPENDICES	A.1
BIODATA OF THE AUTHOR	B.1

LIST OF TABLES

Table		Page
3.1	Summary of the critical Rayleigh number equations derived	3.12
4.1	Settings of the simulation cases for liquid diffusion in liquid	4.14
4.2	Simulation settings for different cases	4.18
5.1	Simulated transient Rayleigh Number and the onset time of convection for top-down liquid diffusion	5.4
5.2	Comparison of the predicted and simulated critical diffusion depth when water diffuses into other liquids	5.10
5.3	Comparison of the predicted and simulated critical wavelength when water diffuses into other liquids	5.11
5.4	Simulated and predicted onset times and critical Rayleigh numbers of incipient instability	5.27

LIST OF FIGURES

Figure		Page
2.1	The three regimes of onset motion for sulphur dioxide-water system observed by Blair and Quinn (1968)	2.7
2.2	Typical elements of flow patterns at the gas-liquid interface (Okhotsimskii and Hozowa, 1998)	2.9
2.3	Flow visualization during carbon dioxide absorption into ethylbenzene and isobutanol by Okhotsimskii and Hozowa (1998)	2.10
2.4	Growth of a two-dimensional perturbation of the uniform state for 1-mm glass beads fluidized by water (Glasser et al., 1997)	2.14
3.1	Development of the concentration gradient induced by top-down transient mass diffusion	3.3
3.2	Flow through particle bed	3.10
4.1	Overview of the segregated solution method	4.3
4.2	Comparison of the grid size effect on the concentration profile	4.9
4.3	The settings of computational domain for the onset of convection when liquid diffuse into liquid	4.14
4.4	The setting of computational domain for the onset of incipient instability caused by liquid flow in particle bed	4.17
5.1	The onset of buoyancy convection caused by diffusion of water in 1-butanol at 10 s	5.2
5.2	Critical transient Rayleigh number for top-down liquid diffusion	5.3
5.3	Comparison of the simulated and predicted onset times of convection for water diffusing into other liquids	5.5
5.4	Series contours of mass fractions and velocity vectors of water for water diffusing into ethyl acetate at 25°C	5.9
5.5	Comparison of the simulated and predicted critical diffusion depth when water diffusing into other liquids	5.10
5.6	Comparison of the simulated and predicted critical wavelength when water diffusing into other liquids	5.11

5.7	Maximum velocity history for water diffusing into 1-butanol	5.12
5.8	Maximum velocity history for water diffusing into ethyl acetate	5.13
5.9	Maximum velocity history for water diffusing into 2-butanone	5.13
5.10	Comparison of the simulated and predicted mass transfer for case A with onset time of convection equal to 10 s	5.14
5.11	Comparison of the simulated and predicted mass transfer coefficient for case A with onset time of convection equal to 10 s	5.15
5.12	Height of the particle bed at various superficial velocities	5.16
5.13	No fluidization observed when superficial velocity is 0.05 m/s or $\sim 0.7 U_{mf}$	5.17
5.14	Fluidization occurred when superficial velocity is 0.073 m/s, U_{mf}	5.18
5.15	Contours of volume fraction of dimethyl phthalate when superficial velocity is 0.292 m/s or $\sim 4 U_{mf}$	5.19
5.16	Series contours of volume fraction of dimethyl phthalate for case 4	5.21
5.17	Series of velocity vectors of dimethyl phthalate for case 4	5.22
5.18	Maximum liquid velocity at the particle bed inlet at $t_c = 0.9$ s (case 3)	5.23
5.19	Maximum liquid velocity at the particle bed inlet with $t_c = 0.6$ s (case 4)	5.24
5.20	Modified critical Rayleigh numbers vs. onset times	5.25
5.21	Modified critical Rayleigh numbers vs. onset times	5.26
5.22	Comparison of the simulated and predicted onset times of incipient instability	5.27

LIST OF ABBREVIATIONS/NOMENCLATURE

α_p	center coefficient
α_{nb}	influence coefficients for the neighboring cells
$\tilde{\alpha}_c$	dimensionless critical wavenumber
A	total area of the cross section of the bed column, m ²
c^*	bulk concentration or saturated concentration of solute, kmol/m ³ or kg/m ³
c^o	initial concentration of solute, kmol/m ³ or kg/m ³
c	concentration, kmol/m ³ or kg/m ³
C_D	drag function
D_b	bed diameter, m
d_p	particle diameter, m
D	diffusivity of mass, m ² /s
E	total energy, J
\vec{F}_q	external body force, N
$\vec{F}_{lift,q}$	lift force, N
$\vec{F}_{v,mq}$	virtual mass force, N
g	gravitational force, m/s ²
h	heat transfer coefficient, W/m ² .K
H	height of the particle bed, m
H	height of simulation chamber, mm
j	mass transfer, kg/m ²
j^o	constant mass flux, kg/m ² .s
k	thermal conductivity, W/m°C
k_{eff}	effective conductivity, W/m.K
K_{sl}	solid-fluid exchange coefficient
K_e	permeability, m ²
m	molality, mol/kg
q	constant heat flux, W/m ²
MW	molecular weight of a component, kg/kmol
Δp	pressure drop across the bed, Pa
R^ϕ	residual

\vec{R}_{pq}	interaction force between phases, N
t	time, s
Δt	time step
u_e	interstitial velocity, m/s
U	superficial velocity of the mass flow, m/s
U_e	interstitial velocity, m/s
U_{mf}	minimum fluidization velocity, m/s
V	molar volume, m ³ /kmol
V°	partial molar volume, m ³ /kmol
V_\emptyset	apparent molar volume, m ³ /kmol
W	weight of the solids in the bed, kg
W	width of simulation chamber, mm
x	mass fraction of component, kg/kg
y	mole fraction of component, kmol/kmol
z	effective distance of the mass diffusion, m

Greek Symbols

ρ	density, kg/m ³
k_{sl}	exchange coefficient
α	molar density coefficient, kg/kmol
β	thermal expansion, 1/K
κ	thermal diffusivity, m ² /s
τ_s	particulate relaxation time, s
ε	porosity
τ_q	q^{th} phase stress-strain, Pa
Ψ	shape factor of particle or sphericity
$v_{r,s}$	terminal velocity correlation for the solid particle
τ	tortuosity
μ	dynamic viscosity, kg/ms
ν	diffusivity of momentum, kinematic viscosity, $= \mu / \rho$, m ² /s
λ	wavelength, m

Abbreviations

LSA	Linear Stability Analysis
FSC	Fixed Surface Concentration
CMF	Constant Mass Flux
Bi	Biot number
Gr	Grashof number
Ra	Rayleigh number
Re	Reynolds number
Sc	Schmidt number

Subscripts

c	critical
c	solid particle bed
f	fluid
n	1-butanol
i	interfacial
o	initial state
p	particle
s	solution of solute and solvent
v	voids
w	water
eff	effective
max	maximum

CHAPTER 1

INTRODUCTION

Mass transfer may produce density gradient that in turn causes free convection. As an example, imagine that a crystal of salt is held just under the surface of initially stagnant water. The salt dissolves and diffuses away from the crystal, producing a solution near the crystal that is denser than the water itself. This solution flows downward, and the resulting flow increases the rate of mass transfer. Thus, mass transfer and flow couple to accelerate dissolution.

The natural convection in a binary gas-liquid system (Okhotsimskii and Hozowa, 1998; Blair and Quinn, 1969) and Maragoni-unstable interfacial turbulence at liquid-liquid interface (Sterling and Scriven, 1959; Orell and Westwater, 1962; Nakaike et al., 1969) have been extensively studied. The transient instability theory of gas diffusion in liquid that leads to the onset of buoyancy convection has been reported by Tan and Thorpe (1996, 1999). However, the case of a Rayleigh-unstable binary liquid system in which the density-driven plume convection happens has attracted much less attention (Berg and Morig, 1969). A new transient Rayleigh number is needed to study the onset of convection induced by liquid diffusion in liquid. The density gradient developed by transient liquid mass diffusion of a solute in a solvent may contribute to the convection accompanying the mass transfer.



The knowledge of natural convection induced by diffusing liquid into a stagnant liquid is of considerable interest because of its importance in the study of mass transfer of liquid solute in solvent for biological and pharmaceutical use, dispersion of effluent in treatment plants and lakes, and other engineering applications. Convection causes more liquid to be dissolved in the solution compared to diffusion.

Fluidization is a two-phase contact process which relies on keeping up the grains of solid substance in suspension state in the flux flowing up with appropriate velocity. The fluidization plays an essential role in many engineering processes because intensive mixing of phases is conducive to all sorts of diffusion phenomena, such as: intensive exchange of mass and heat, generation of uniform field of temperatures, etc.

The linear stability analysis (LSA) was first employed by Jackson (1963) to study the onset of incipient instability by assuming a convection mechanism. The inertia force of the particle imparted by average fluid velocity was found to contribute to the instability. Past researches considered the increase of voidage as an indicator of the onset of fluidization, although the expansion of voidage is in fact a consequence of fluidization of the bed.

The main cause of incipient fluidization is the momentum of the high incoming flux that overcomes the buoyancy force of the solid particles. Moreover, the incipient



instability is preceded by the flowing of the liquid into the interstices of the particle bed with a mass flux or superficial velocity exceeding the minimum fluidization velocity, U_{mf} . Therefore the first abrupt increase of flow velocity should be the indicator of the onset of incipient fluidization when the localized saturation of the interstices is sufficient to lift the particles. The onset of incipient fluidization caused by liquid flow in particle bed is coupled with the immense change of mass fraction of the liquid in the region close to the flow inlet.

The objectives of this work are to study the onset of convection caused by liquid diffusion in liquid and the onset of incipient instability caused by liquid flow in particle bed. A critical Rayleigh number will be derived for the prediction of the onset of buoyancy convection when water diffuses into various partially miscible organic liquids at different temperatures. For the onset of incipient instability of liquid flow in particle, a critical Rayleigh number based on momentum diffusion will be derived. The derivation performed in this study follow closely the principle of transient instability theories advanced by Tan and Thorpe (1996 and 1999) and Tan (2004).

Two-dimensional time-dependent simulations will be conducted to verify the principles of transient instability. The onset of buoyancy convection induced by liquid mass diffusion and the mechanism of incipient instability in a particle bed will be simulated using a CFD package, FLUENT. Parameters such as the onset time of

instability, critical diffusion depth, size of the plume and critical Rayleigh number will be obtained from simulations.

This study predicts the particular mass transfer parameters for liquid diffusion in liquid as well as liquid flow in particle bed without conducting the real experiments. These experiments are hardly to be carried out as advanced technology and equipments are required. The simulated design of experiment in this research may shed some light for the experiment models.

CHAPTER 2

LITERATURE REVIEW

2.1 Introduction

The theory of transient convection and instabilities will first be reviewed. This is followed by the discussion of the experimental studies of convective instability induced by adverse density gradient. The typical convection patterns are presented. Finally, discussions on the instability and flow pattern in liquid fluidized bed are given.

2.2 Theory of Transient Convection and Instabilities

Lord Rayleigh (1916) derived a criterion for the onset of buoyancy convection in a fluid layer bounded by two free surfaces based on an adverse linear temperature gradient typical of steady-state heat transport; the stability criterion is rearranged later to become the well-known Rayleigh number,

$$Ra = \frac{g\beta d^3 \Delta T}{\nu \kappa} \quad (2.1)$$

where g is the gravitational acceleration, β is the thermal expansion, d is the depth of fluid layer, ΔT is the temperature difference of two surfaces, ν is the kinematic viscosity and κ is the thermal diffusivity.

However, natural convection is induced by a time-dependent and non-linear temperature profile. Several definitions of time-dependent Rayleigh number were suggested by Howard (1964) and Davenport and King (1972), but none of them has